



SPECIFICATION SHEET

Item nr. 2508

Available sizes : from 34 to 47

CE Mark : 
UNI EN ISO 20347:2012 OB A E FO SRC

MADE IN ITALY

Item description: Unisex clog, full grain leather upper, we can supply white and all the other colours of catalogue, but the outsole color is always white.

Packaging, storage, maintenance and life: The shoes are packed in boxes and must be stored in warehouse at room temperature.

Due to several factors (humidity during storage and modification of the structure of the materials in time), it is not possible to indicate an expiry date. The lasting of the footwear is due to the correct utilization.

The footwear must be used in fit environments, they must have a daily maintenance and a storage during the rest in suitable local. They must not have submitted to particular stress what sources of high heat or cold, immersion in water or other liquids, will have to superficially be cleaned only with brushes with soft bristles or plotted soft and same leather colour polish

Components:

Upper: : Genuine full grain bovine leather upper, breathable and abrasion resistant, with perforation;

Fastening: back strap for regulation

Lining: Special textile with high abrasion resistance, highly breathable.

Sock : true leather sock, highly capability of absorption and de-absorption of water (sweat).

Toe reinforcement with TNT fibers inserted between vamp upper and vamp lining.

Collar: padded collar with foam lined with special fabric imitation leather.

Sole : Sole bottom is high density Polyurethane, antistatic, abrasion resistant.

Slip Resistance: The sole bottom resists to the slip risk in accordance with UNI EN ISO 20347:2012 with requirement SRC

Heel : the heel is incorporated in the sole, and it has the property to absorb energy of seat region more than 20 Joules. it is recommended for the correct body weight absorption.

The whole upper of the footwear is sewn with thread highly resistant. The construction is cemented: the upper and insole is cemented to the sole.



Supplementary requirements:

A: Anti-static properties

E: Energy absorption of the seat region

FO: Fuel-oil resistant outsole

SRC: Slip resistance