



SPECIFICATION SHEET

Item nr. **2705**

Available sizes :

Singular size from 34 to 42, double size 43/44, 45/46, 47/48



CE Mark :
UNI EN ISO 20347:2012 OB A E SRC

MADE IN ITALY

Item description: Professional clog, Unisex, upper perforated only in the lateral low part of the product, not perforated in the upper side, to keep feet fresh, arch support.

Packaging, storage, maintenance and life: The shoes are packed in boxes and must be stored in warehouse at room temperature.

Due to several factors (humidity during storage and modification of the structure of the materials in time), it is not possible to indicate an expiry date. The lasting of the footwear is due to the correct utilization.

The footwears must be used in fit environments, they must have a daily maintenance and a storage during the rest in suitable local. They must not have submitted to particular stress what sources of high heat or cold. The clog can be washed in autoclave and be sterilized with a disinfectant solution or at 135°C for 120 minutes

Components:

Upper and sole: SEBS Thermoplastic polymer Injected – latex free – Monobloc

Heel : the heel is incorporated in the sole, and it has the property to absorb Energy of seat region (shock absorber) more than 20 Joules. it is recommended for the correct body weight absorption.

Insock: we can supply with or without anatomic removable insock, washable in washing machine up to 40°C.

Sterilization: The clog can be washed in autoclave and be sterilized with a disinfectant solution or at 135°C for 120 minutes and respect the normative prEN 13832-1:2004 concerning the sterilization resistance. It can support about 600 sterilization cycles.

Normative: The clog respects the necessary requirements according to the European Regulation 89/686/CEE, regarding personal safety devices.

The clog respects the international regulations ISO 7232 (86) regarding antistatic shoes

The footwear complies with what prescribed by UNI EN ISO 20347:2012 concerning the slip resistance of the outsole with requirement SRC

Available colours: BN01, RS30, VR10, BL20, GL40, RS33, GL41, BL22 (listed here on the right)

Supplementary requirements:

A: Anti-static properties

E: Energy absorption of the seat region

SRC: Slip resistance



Colour ref. BL20

