



## SPECIFICATION SHEET

**Item nr.** 2721

**Available sizes:** from 35 to 47

**CE Mark:**   
UNI EN ISO 20347:2012 OB A E SRC

**Item description:** Professional clog, Unisex, EXTRA-LIGHT, average weight 220 grams./pair, available colour white, green, blue, light blue, orange, fuxia, black, made in accordance with European standard EN ISO 20347

**Packaging, storage, maintenance and life:** The shoes are packed in boxes and must be stored in warehouse at room temperature.

Due to several factors (humidity during storage and modification of the structure of the materials in time), it is not possible to indicate an expiry date.

The lasting of the footwear is due to the correct utilization.

The footwear must be used in fit environments, they must have a daily maintenance and a storage during the rest in suitable local. They must not have submitted to particular stress what sources of high heat or cold.

### Components:

**Upper and sole:** E.V.A., antistatic, anti abrasion, is made of an extremely light material (average weight: 220 grams./pair) that guarantees a comfortable fit and adaptation to the foot even when a prolonged standing or walking is required. The lateral holes are designed to provide breathability but to avoid liquid filtration.

**Fastening:** back strap for regulation, movable, available also personalized buckle (for big quantity)

**Heel :** the heel is incorporated in the sole, and it has the property to absorb Energy of seat region more than 20 Joules. it is recommended for the correct body weight absorption.

**Antistatic :** antistatic no marking element in the heel zone, efficient even after many washings.

**Cleaning:** The clog can be washed in washing machine up to 50°C. with normal sanitizing detergents.

**Insock:** we can supply with or without anatomic removable insock.

**Antislip sole:** The footwear complies with what prescribed by UNI EN ISO 20347:2012 concerning the slip resistance of the outsole with requirement SRC

#### **Supplementary requirements:**

**A:** anti-static properties (antistatic element in neutral color, no marking on floor).

**E:** energy absorption of the seat region

**SRC:** Slip resistance

