

Item nr.

400

Available sizes :

from 35 to 47

CE Mark : **CE** UNI EN ISO 20347:2012 O2 FO SRC

SPECIFICATION SHEET

Item description: Unisex shoe, available colour white.

Packaging, storage, maintenance and life: The shoes are packed in boxes and must be stored in warehouse at room temperature.

Due to several factors (humidity during storage and modification of the structure of the materials in time), it is not possible to indicate an expiry date. The lasting of the footwear is due to the correct utilization.

The footwear must be used in fit environments, they must have a daily maintenance and a storage during the rest in suitable local. They must not have submitted to particular stress what sources of high heat or cold, immersion in water or other liquids, will have to superficially be cleaned with brushes or wet sponge, or washing in washing machine up to 30° C

Components:

Upper: Microfiber upper, white colour, water resistance of the upper, waterproof and breathable.

Lining: special textil with high abrasion resistance, highly breathable.

Insole: the insock is composed by a special TNT with highly capability of absorption and desorption of water (sweat).

Insock: anatomic removable insock.

Toe reinforcement: with TNT fibers inserted between vamp upper and vamp lining

Heel reinforcement: with composition leather inserted between quarter/upper and quarter/lining

Fastening: closing by velcro

Sole: Sole bottom is polyurethane, abrasion resistant, anti-static, oil and fuel resistant.

Heel: the heel is incorporated in the sole, and it has the property to absorb Energy of seat region more than 20 Joules. it is recommended for the correct body weight absorption

Slip Resistance: The sole bottom resists to the slip risk in accordance with EN ISO 20347 with requirement SRC.

The whole footwear is sewn with thread highly resistant. The construction is injected.



Supplementary requirements:

A: Anti-static properties
E: Energy absorption of the seat region
WRU: Water resistant upper
FO: Fuel-oil resistant outsole
SRC: Slip resistance