



SPECIFICATION SHEET

Item nr. 408
Available sizes : from 35 to 47

CE Mark : 
UNI EN ISO 20345:2012 S3 SRC

Item description: Professional shoe, available colour black.

Packaging, storage, maintenance and life: The shoes are packed in boxes and must be stored in warehouse at room temperature.

Due to several factors (humidity during storage and modification of the structure of the materials in time), it is not possible to indicate an expiry date. The lasting of the footwear is due to the correct utilization.

The footwear must be used in fit environments, they must have a daily maintenance and a storage during the rest in suitable local. They must not have submitted to particular stress what sources of high heat or cold, immersion in water or other liquids, will have to superficially be cleaned with brushes or wet sponge.

Components:

Upper : genuine leather, breathable and waterproof, with high tear strength resistance, color black.

Lining: special fabric, breathable and abrasion resistant

Insole : the insole is composed by special fibers with very high resistance to the abrasion, antistatic, and this special insole resists to the perforation at more than 1100 N, in accordance with EN ISO 20345

Composit toe cap: the protection of the toes is made by a special TOECAP made by synthetic material, light and resistant to an energy level of at least 200 J

Heel reinforcement, with synthetic material, inserted between quarter/upper and quarter/lining

Fastening : lacing with eyelets and laces.

Seat sock : anatomic removable insock, made in soft polyurethane with fabric lining.

Sole polyurethane, antistatic, oil resistant, abrasion resistant.

Slip resistance: in accordance with the Standard UNI EN ISO 20345:2012 with the value of SRC.

Heel : the heel is incorporated in the sole, and it has the property to absorb Energy of seat region more than 20 Joules. it is recommended for the correct body weight absorption.

The whole footwear is sewn with thread highly resistant. The construction is by injection of the sole bottom directly to the sock and upper.



Supplementary requirements:

A: Anti-static properties

E: Energy absorption of the seat region

WRU: Water resistant upper

SRC: Slip resistance