



SPECIFICATION SHEET

Item nr. 46416

Available sizes : from 35 to 43

CE Mark: 
UNI EN ISO 20347:2012 O2 HRO FO SRC

MADE IN ITALY

Item description: Woman boot, leather upper, available colour black.

Packaging, storage, maintenance and life: The shoes are packed in boxes and must be stored in warehouse at room temperature.

Due to several factors (humidity during storage and modification of the structure of the materials in time), it is not possible to indicate an expiry date. The lasting of the footwear is due to the correct utilization.

The footwears must be used in fit environments, they must have a daily maintenance and a storage during the rest in suitable local. They must not have submitted to particular stress what sources of high heat or cold, immersion in water or other liquids, will have to superficially be cleaned only with brushes with soft bristles or plotted soft and same leather colour polish

Components:

Upper: : Genuine full grain bovine leather upper, waterproof and breathable abrasion resistant.

Lining: Genuine leather, natural colour, breathable and abrasion resistant

Insole : is composed by a special anti-static natural fiber with highly capability of absorption and de-absorption of water (sweat), with perforations for Klimacomfort System performance.

Removable insock: The shoe is supplied with a removable insock, the superior part is lined with leather on soft synthetic body with particular characteristic of energy absorption in the seat region.

Toe reinforcement with TNT fibers inserted between vamp upper and vamp lining

Heel reinforcement, with composition leather inserted between quarter/upper and quarter/lining

Fastening : with zipper, on the lateral internal side, elastic in the external side, covered with leather.

Sole : Nitril rubber with high resistance to the abrasion, fuel oil resistance, hot contact resistance, anti-static, abrasion resistant, with the special system « Klimacomfort » that guarantees a real change of air inside the shoe, above all in the most critical points, under foot plant ant tip, where sweat accumulates most. While one's walking a pump ejects stuffy air through a valve situated in interior side of the heel.

Slip Resistance: The sole bottom resists to the slip risk in accordance with EN ISO 20347:2004/Amd 1:2007 with requirement SRC

Heel : the heel is incorporated in the sole, and it has the property to absorb energy of seat region more than 20 Joules. it is recommended for the correct body weight absorption.

The whole upper of the footwear is sewn with thread highly resistant. The construction is cemented: the upper and insole is cemented to the sole.



Supplementary requirements:

A: Anti-static properties

E: Energy absorption of the seat region

WRU: Water resistant upper

HRO: Heat resistant outsole

FO: Fuel-oil resistant outsole

SRC: Slip resistance