



SPECIFICATION SHEET

Item nr. 46527
Available sizes: from 35 to 48

CE Mark : 
UNI EN ISO 20347:2012 O3 HI CI WR AN HRO
FO SRC

MADE IN ITALY

Item description: Man derby boot, leather upper, available colour black. This special boot is made to be used in all the particular situations where there is a concrete risk and there is the need to protect the foot and the inferior part of the leg from many dangerous factors: Perforation of the bottom, Protection of the ankle, Rapid fastening for a rapid dressing.

Packaging, storage, maintenance and life: The shoes are packed in boxes and must be stored in warehouse at room temperature.

Due to several factors (humidity during storage and modification of the structure of the materials in time), it is not possible to indicate an expiry date. The lasting of the footwear is due to the correct utilization.

The footwear must be used in fit environments, they must have a daily maintenance and a storage during the rest in suitable local. They must not have submitted to particular stress what sources of high heat or cold, immersion in water or other liquids, will have to superficially be cleaned only with brushes with soft bristles or plotted soft and same leather colour polish

Components:

Upper: Genuine waterproof and breathable calf leather upper, tear strength resistance more that 120 N.

Vamp and quarter Lining: Special synthetic lining, water resistant and breathable membrane, cold and heat insulation, with particular treatment to have a long lasting antibacterial property inside the boot. Seams are protected by welded seams, with a special thermal adhesive tape.

Ankle protection with 2 special synthetic dish with foam padding in the internal and external side of the boot, this protection is tested in accordance with EN ISO 20347 standard

Insole: TNT antistatic special insole with high capability of absorption and desorption of water, thickness more that 2,0 mm; The whole footwear resists to the penetration of the sole in accordance with UNI EN ISO 20344:2012 standard, that requires a resistance to a force not less than 1100 N.

Removable insock: The boot is supplied with a removable insock in Polyurethane body with fenestration useful to create pockets, intermediate cork layer, and soft fabric in contact with the foot.

Toe reinforcement with TNT fibers inserted between vamp upper and vamp lining

Heel reinforcement, with composition leather inserted between quarter/upper and quarter/lining

Fastening : The fastening is by special textiles lacing, the boot can be worn and quickly removed through the use of the present metallic zipper in the central part of the lacing

Outsole: rubber with high resistance to the abrasion, antistatic, fuel oil resistance, hot contact resistance.



Supplementary requirements:

A: Anti-static properties

E: Energy absorption of the seat region

WRU: Water resistant upper

Slip Resistance: The sole bottom resists to the slip risk in accordance with UNI EN ISO 20347:2012 with requirement SRC

Heel : the heel is incorporated in the sole, and it has the property to absorb energy of seat region more than 20 Joules. it is recommended for the correct body weight absorption.

The whole upper of the footwear is sewn with thread highly resistant. The construction is cemented: the upper and insole is cemented to the sole.

P: Penetration resistant outsole

HI: Insulation against heat

CI: Insulation against cold

WR: Waterproof footwear

AN: Ankle protection

HRO: Heat resistant outsole

FO: Fuel-oil resistant outsole

SRC: Slip resistance