



SPECIFICATION SHEET

Item nr. 46716

Available sizes : from 38 to 48

CE Mark : 
UNI EN ISO 20345:2012 S2 HRO SRC

MADE IN ITALY

Item description: Men safety ankle boot, leather upper, available colour black.

Packaging, storage, maintenance and life: The shoes are packed in boxes and must be stored in warehouse at room temperature.

Due to several factors (humidity during storage and modification of the structure of the materials in time), it is not possible to indicate an expiry date. The lasting of the footwear is due to the correct utilization.

The footwears must be used in fit environments, they must have a daily maintenance and a storage during the rest in suitable local. They must not have submitted to particular stress what sources of high heat or cold, immersion in water or other liquids, will have to superficially be cleaned only with brushes with soft bristles or plotted soft and same leather colour polish

Components:

Upper: genuine leather, soft, smooth surface, breathable and waterproof, with high tear strength resistance, color black.

Vamp Lining: Special textile with high abrasion resistance, highly breathable

Quarter Lining: special fabric, breathable and abrasion resistant.

Insole: is composed by a special anti-static natural fiber with highly capability of absorption and de-absorption of water (sweat), the surface is of genuine leather.

Seat sock: Special fabric, with anatomic foam.

Toe reinforcement: steel toe cap, for protection of the fingers, with resistance to the shock of 200 J

Heel counter reinforcement: with synthetic material, inserted between quarter/upper and quarter/lining

Fastening: with 8 holes and laces each shoe

Sole: rubber sole with high resistance to the abrasion, antistatic, fuel oil resistance, heat resistance.

Slip Resistance: The sole bottom resists to the slip risk in accordance with UNI EN ISO 20345 requirement SRC

Heel : the heel is incorporated in the sole, and it has the property to absorb energy of seat region more than 20 Joules, in accordance with UNI EN ISO 20344; it is recommended for the correct body weight absorption.

The whole upper of the footwear is sewn with thread highly resistant. The construction is cemented: the upper and insole is cemented to the sole.



Supplementary requirements:

A: Anti-static properties

E: Energy absorption of the seat region

WRU: Water resistant upper

FO: Fuel-oil resistant outsole

HRO: Heat resistant outsole

SRC: Slip resistance