



SPECIFICATION SHEET

Item nr. 46810

Available sizes : from 35 to 48

CE Mark: 
UNI EN ISO 20347:2012 O2 HI CI WR HRO FO
SRC

MADE IN ITALY

Item description: Unisex boot, leather upper, available colour black. This special boot is made to be used in all the particular situations where there is a concrete risk and there is the need to protect the foot and the inferior part of the leg from many dangerous factors.

Packaging, storage, maintenance and life: The shoes are packed in boxes and must be stored in warehouse at room temperature.

Due to several factors (humidity during storage and modification of the structure of the materials in time), it is not possible to indicate an expiry date.

The lasting of the footwear is due to the correct utilization.

The footwear must be used in fit environments, they must have a daily maintenance and a storage during the rest in suitable local. They must not have submitted to particular stress what sources of high heat or cold, immersion in water or other liquids, will have to superficially be cleaned only with brushes with soft bristles or plotted soft and same leather colour polish

Components:

Upper: Genuine waterproof and breathable bovine leather upper.

Lining: Special synthetic lining, water resistant and breathable membrane, cold and heat insulation, with particular treatment to have a long lasting antibacterial property inside the boot. Seams are protected by a special thermal adhesive tape.

Insole: TNT antistatic special insole with high capability of absorption and desorption of water.

Removable insock: The boot is supplied with a special removable insock that is composed by Polyurethane body with particular Gel in the heel area to increase energy absorption, padded with Memory foam, lined with a special antibacterial fabric.

Toe reinforcement with TNT fibers inserted between vamp upper and vamp lining

Heel reinforcement, with composition leather inserted between quarter/upper and quarter/lining

Fastening: by lacing and lateral zipper in the internal side. The boot can be worn and quickly removed through the use of the lateral zipper.

Outsole: the sole is made by 2 components – internal component soft Poliurethane to better absorb the body weight, external surface in nitril rubber with high resistance to the abrasion, fuel oil resistance, hot contact resistance, with the special system « Klimacomfort » that guarantees a real change of air inside the shoe, above all in the most critical points, under foot plant ant tip, where sweat accumulates most. While one's walking a pump ejects stuffy air through a valve situated in interior side of the heel.

Slip Resistance: The sole bottom resists to the slip risk in accordance with UNI EN ISO 20347:2012 with requirement SRC

Heel: the heel is incorporated in the sole, and it has the property to absorb energy of seat region more than 20 Joules. It is recommended for the correct body weight absorption.

The whole upper of the footwear is sewn with thread highly resistant. The construction is cemented: the upper and insole are cemented to the sole.



A: Anti-static properties

E: Energy absorption of the seat region

WRU: Water resistant upper

HI: Insulation against heat

CI: Insulation against cold

WR: Waterproof footwear

HRO: Heat resistant outsole

FO: Fuel-oil resistant outsole

SRC: Slip resistance