



SPECIFICATION SHEET

Item nr **46837**

Available sizes: **from 34 to 47**

CE Mark: **CE**
UNI EN ISO 20347:2012 O1 FO SRC

Item description: Unisex Professional Shoe, sneaker model, laced with 3 pairs of fabric loops and closure system with elastic strings with lace lock.

Packaging, storage, maintenance and life: The shoes are packed in boxes and must be stored in warehouse at room temperature.

Due to several factors (humidity during storage and modification of the structure of the materials in time), it is not possible to indicate an expiry date.

The lasting of the footwear is due to the correct utilization.

The footwear must be used in fit environments, they must have a daily maintenance and a storage during the rest in suitable local.

The shoe will have to superficially be cleaned with brushes or wet sponge, or is washable in washing machine up to 40°C.

Components:

Upper: Microfiber and technical fabric, extremely breathable.

Lining: special textile with high abrasion resistance, highly breathable.

Insole: the insole is composed by a special TNT with highly capability of absorption and desorption of water (sweat).

Sole: Extra-Light EVA sole, slip resistance, abrasion resistance, fuel oil resistance, with ESD antistatic insert in the heel area, extremely light and flexible.

Slip Resistance: The sole bottom resists to the slip risk in accordance with UNI EN ISO 20347:2012 with requirement SRC.

Heel: the heel is incorporated in the sole, and it has the property to absorb Energy of seat region more than 20 Joules. it is recommended for the correct body weight absorption

Removable insock: ESD antistatic polyurethane insock lined with breathable fabric.



Supplementary requirements:

A: Anti-static properties

E: Energy absorption of the seat region

FO: Fuel-oil resistant outsole

SRC: Slip resistance