




SPECIFICATION SHEET

Item nr. 498

Available sizes: from 34 to 48

CE Mark: 
UNI EN ISO 20347:2012 O3 FO SRC

MADE IN ITALY

Item description: Professional boot, available colour black.

Packaging, storage, maintenance and life: The shoes are packed in boxes and must be stored in warehouse at room temperature. Due to several factors (humidity during storage and modification of the structure of the materials in time), it is not possible to indicate an expiry date. The lasting of the footwear is due to the correct utilization. The footwear must be used in fit environments, they must have a daily maintenance and a storage during the rest in suitable local. They must not have submitted to particular stress what sources of high heat or cold, immersion in water or other liquids, will have to superficially be cleaned with brushes or wet sponge.

Components:

Upper: Full grain leather and technical fabric, breathable and waterproof, with high tear strength resistance, color black.

Lining: special fabric, breathable and abrasion resistant.

Insole: the insole is composed by special fibers with very high resistance to the abrasion, antistatic, and this special insole resists to the perforation at more than 1100 N, in accordance with UNI EN ISO 20347:2012

Toe reinforcement with TNT fibers inserted between vamp upper and vamp lining

Heel reinforcement, with synthetic material, inserted between quarter/upper and quarter/lining

Fastening: lacing with eyelets and laces and zipper in the front part of the boot.

Seat sock: anatomic removable insock, made in soft polyurethane with fabric and completely perforated for better breathability.

Sole polyurethane, antistatic, oil resistant, abrasion resistant.

Slip resistance: in accordance with the Standard UNI EN ISO 20347:2012 with the value of SRC.

Heel: the heel is incorporated in the sole, and it has the property to absorb Energy of seat region more than 20 Joules, it is recommended for the correct body weight absorption.

The whole footwear is sewn with thread highly resistant. The construction is by injection of the sole bottom directly to the sock and upper.



Supplementary requirements:

A: Anti-static properties

E: Energy absorption of the seat region

WRU: Water resistant upper

P: Penetration resistant outsole

FO: Fuel-oil resistant outsole

SRC: Slip resistance